REFERENCES

Andreas Lanitis, Christopher J. Taylor and Timothy Francis Cootes (1997)" Automatic Interpretation and Coding of Face Images using Flexible Model". IEEE Tran. On Pattern Analysis and Machine Intelligence, 19(7):743-756.

B. Scholkopf, A. Smola and K.-R.Muller (1998)"nonlinear component analysis as a kernel Eigen value problem", Neural Computation, 10:1299–1319.

B. Li and R. Chellappa (2001)"Face verification through tracking facial features", J. Opt. Soc. Am18:2969–2981.

C.-W. Tan and A. Kumar (June 2011) "Automated segmentation of iris images using visible wavelength face images," Proc. CVPR 2011, pp. 9-14, Colorado Springs, CVPRW'11.

C. E. Thomaz, R. Q. Feitosa and A. Veiga (1998) Design of Radial Basis Function Network as Classifier in face Recognition using Eigenfaces. In Vth Brazilian Symposium on Neural Networks, pages 118-123.

E. Krichen, S. Garcia-Salicetti and B. Dorizzi (2007)" A new probabilistic iris quality measure for comprehensive noise detection," IEEE Conference on Biometrics: Theory, Applications and Systems, BTAS'07, pp. IEEE Systems; Man and Cybernetics Society.

G. Aggarwal, A. R. Chowdhury and R. Chellappa (2004)" system identification approach for video-based face recognition." In Proc. 17th Int. Conf. Pattern Recognition, volume 1, pages 175–178.

H. Proenca and L. Alexandre (April 2007)"Toward noncooperative iris recognition: A classification approach using multiple signatures," Pattern Analysis and Machine Intelligence, IEEE Transactions on, vol. 29, pp. 607 -612.

H. Proenca and L. Alexandre (2006/04/06)"Iris segmentation methodology for noncooperative recognition," IEE Proceedings-Vision, Image and Signal Pro- cessing, vol. 153, no. 2, pp. 199 - 205

H. Proenca, (2010) “Iris recognition: On the segmentation of degraded images acquired in the visible Wavelength,” IEEE Trans. Pattern Anal. Mach. Intell., vol. 32, no. 8, pp. 1502–1516.

J. Pillai, V. Patel, R. Chellappa and N. Ratha, (Sept. 2011) “Secure and robust iris recognition using random projections and sparse representations," Pattern Analysis and Machine Intelligence, IEEE Transactions on, vol. 33, pp. 1877 -1893.

J. G. Daugman, (November 1993) High confidence visual recognition of persons by a test of statistical independence, IEEE Transactions on Pattern Analysis and Machine Intelligence, 15(11), 1148–1161.

J. Huang (May1998) Detection Strategies for Face Recognition Using Learning and Evolution. PhD thesis, George Mason University.

J. Thornton, M. Savvides, and V. Kumar (April 2007),”A Bayesian approach to deformed pattern matching of iris images," Pattern Analysis and Machine Intelligence, IEEE Transactions on, vol. 29, pp. 596 -606.

J.Shutler“ComplexZernikemoments,(2002).http://homepages.inf.ed.ac.uk/rbf/CVonline/LOCAL_COPIES/SHUTLER3/node11.html

K. Hollingsworth, K. Bowyer, and P. Flynn (2009/01/) “Pupil dilation degrades iris biometric performance" Computer Vision and Image Understanding, vol. 113, no. 1, pp. 150 -157.

K. C. Lee, J. Ho, M. H. Yang, and D. Kriegman (2003) ” Video-based face recognition using probabilistic appearance manifolds”, In Proc. Computer Vision and Pattern Recognition, pages 313–320.

K. Haris and Efstratiadis (1998) “Hybrid Image Segmentation Using Watershed and Fast Region Merging,” IEEE Trans. Image Process, vol. 7, no. 12, pp. 1684-1699.

Li S.Z., Chu R. Ao M., Zhang L. He. R. (2006)” Highly accurate and fast face recognition using near infrared images”, In International Conference on Biometrics (ICB 2006), pp. 151–158.

L. S Stanislav and RaFsi (2000) “A Fast Watershed Algorithm Based on Rain falling Simulation”, in proce. Of 8th Int. Conf. on Computer Graphics, Visualization, and Interactive Digital Media, vol. 1, pp. 100-107.

L. Ma, T. Tan, Y. Wang, and D. Zhang (2003/12/) ”Personal identification based on iris texture analysis," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 25, no. 12, pp. 1519 – 1533.

L. Masek (2006) “Recognition of Human Iris Patterns for Biometric Identification”, M.S. Dissertation, the University of Western Australia.

Moghaddam B. T. Jebara, and A. Pentland (2000)” Bayesian face recognition. Pattern Recognition”, 33(11):1771–1782.

M. A. Turk and A. P. Pentland (1991)” Eigenfaces for recognition”, J. Cognitive Neurosci.3 (1):71–86.

N. Kalka, J. Zuo, N. Schmid, and B. Cukic (2010)”Estimating and fusing quality factors for iris biometric images," IEEE Transactions on Systems, Man, and Cybernetics Part A: Systems and Humans, vol. 40, no. 3, pp. 509 – 524.

N.B. Puhan, N. Sudha, A. Sivaraman Kaushalram (2011) ” Efficient segmentation technique for noisy frontal view iris images using Fourier spectral density”, Signal, Image and Video Processing, 5, p. 105.

R. Brunelli and T. Poggio (October 1993)” Face Recognition: Features versus Templates. IEEE Tran. On Pattern Analysis and Machine Intelligence, 15(10):1042-1052.

R. Wildes, J. Asmuth, G. Green, S. Hsu, R. Kolczynski, J. Matey, & S. McBride (1996) ” A Machine vision System for Iris Recognition”, Machine Vision and Applications, 9(1), 1-8.

Rajesh M. Bodade, Dr. Snajay N. Talbar, Lt. Shailendra K. Ojha (2008 IEEE) Iris Recognition using Rotational Complex Wavelet Filters: A Novel Apporach, 978-1-4244-3397-1/08.

Rattani A. Tistarelli M. (2009) ” Robust multi-modal and multi-unit feature level fusion of face and iris biometrics.”, In: M. Tistarelli, M. Nixon (eds.) Advances in Biometrics, Lecture Notes in Computer Science, vol. 5558, pp. 960–969. Springer Berlin / Heidelberg

S. Zhou and R. Chellappa (2002) “Probabilistic human recognition from video”,Proc. 7th EuropeanConf. Computer Vision, Vol. III, pages 681–697.

Son B. Lee Y (2003) ” Biometric authentication system using reduced joint feature vector of iris and face”, In: T. Kanade, A. Jain, N. Ratha (eds.) 6th International Conference on Audio and Video-Based Biometric Person Authentication (AVBPA’03), Lecture Notes in Computer Science. Springer Berlin / Heidelberg

S. Z. Li and A. K. Jain (2009) Encyclopedia of Biometrics, ch. Anatomy of eyes, pp. 43-46. Springer Science Business Media, LLC.

T. Tan, Z. He, and Z. Sun (2010) “Efficient and robust segmentation of noisy iris images for non-cooperative iris recognition,” Image Vis. Comput., vol. 28, no. 2, pp. 223–230.

V. N. Vapnik (1998) “Statistical Learning Theory”. Wiley, New York.

L.Wiskott J.M. Fellous and C. von der Malsburg (1997) “Face recognition by elastic bunch graph matching”, IEEE Trans. Pattern Analysis and Machine Intell., 19(7):775–779.

Wang Y., Tan T., Jain A.K (2003) “Combining face and iris biometrics for identity verification”, In:4th International Conference on Audio- and Video-Based Biometric Person Authentication(AVBPA’03), pp. 805–813. Springer-Verlag, Berlin, Heidelberg.

W. H. Tan, M. Bister and G. Coatrieux (2006) “Uncommitted Morphological Merging of Watershed Segments,” Proc. 2nd IEEE Int. Conf. on Information & Communication Technologies: from Theory to Applications, vol. 1, pp. 1573 – 1577.

X. Liu and T. Chen (2003)”Video-based face recognition using adaptive hidden markov models”, In Proc. Computer Vision and Pattern Recognition, pages 340–345.

Y. Chen, S. C. Dass and A. K. Jain (2006) “Localized iris image quality using 2-d wavelets," Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics),vol. 3832 LNCS, pp. 373 – 381.

Yang J., Liao S., Li S (2009) ”Automatic partial face alignment in nir video sequences. In:M. Tistarelli, M. Nixon (eds.) Advances in Biometrics, Lecture Notes in Computer Science, vol. 5558, pp. 249–258. Springer Berlin / Heidelberg.

Zhang Z. Wang R. Pan K. Li S. Zhang P (2007)” Fusion of near infrared face and iris biometrics” In: S.W. Lee, S. Li (eds.) Advances in Biometrics, Lecture Notes in Computer Science, vol. 4642, pp. 172–180. Springer Berlin / Heidelberg.